



L Series

Box Style Highpass Filter



PC mountable or connector. Competitive form fit with broad range and complexity.

Overview

| | Standard Parameters | Special Parameters | Comments |
|-----------------------|-----------------------|----------------------------|---|
| 3 dB Cutoff Frequency | 60 to 1500 MHz | 5 to 3500 MHz | |
| Upper Passband Limit | ~ 5x Cutoff Frequency | Determined by Design | |
| Maximum VSWR | 1.5:1 | 1.2:1 | |
| Average Input Power | 0.5 Watts | Up to 2.5 Watts | Measured up to 10,000 feet |
| Maximum Attenuation | Up to 50 dBa | Up to 65 dBa | |
| Topology | Chebyshev | *Consult Factory | |
| Nominal Impedance | 50 Ohms | **Consult Factory | |
| Number of Sections | 5 | 10 | |
| Shock | 5 G's | Up to 500 G's | See Below |
| Vibration | 5 G's | Up to 500 G's | See Below |
| Humidity | 90%, non-condensing | Up to 100%, non-condensing | See Below |
| Altitude | Unlimited | Unlimited | See Below |
| Operating Temperature | 0 to +50 °Celsius | -55 to +125 °Celsius | See Below |
| Storage Temperature | -55 to +85 °Celsius | -65 to +150 °Celsius | See Below |
| Gross Leak | As required | As required | Additional testing charges will apply |
| Fine Leak | As required | As required | Additional testing charges will apply |
| Moisure Resistance | 100% | 100% | |
| Mounting Options | PC Mount | Connectorized | Gross and Fine Leak do not apply to connectorized parts |
| Connector Options | SMA Female or Male | | |

Number of Sections *** Dimensions

| Number of Sections *** | Dimensions |
|------------------------|-----------------------|
| 2 to 3 | 0.75" x 0.50" x 0.40" |
| 4 to 5 | 1.00" x 0.50" x 0.40" |
| 6 to 7 | 1.50" x 0.50" x 0.40" |
| 8 to 10 | 2.00" x 0.50" x 0.40" |

Other parameters may be specified. Please consult factory for any deviation from standard.

*Other topologies are available upon request or design need. These can include, but are not limited to: Gaussian, Butterworth, Bessel, Elliptical, and Pole-placed designs.

**Other impedances can be achieved, but the package is designed as a 50 Ohm unit. Matching to any other impedance will need prior approval and may not be guaranteed.

***Dependant upon frequency range and design requirements. Exact size to be quoted by factory.

Any environmental testing will incur additional charges. Consult factory for costs associated with environmental testing. All filters can be "Designed to" and may not require the additional testing. Each application will be different.

Need help now? Visit Mtronpti.com and click...

 [Request a Quote](#)  [Find a Rep or Distributor](#)  [Contact](#)

Orlando

2525 Shader Rd
Orlando, FL 32804 USA
Phone: 407-298-2000
Fax: 407-293-2979

Shanghai

Room 2215, 22/F
Tomson Commercial Building
710 Dongfang Road
Pudong, Shanghai, China
Phone: 86-21-6165-2282
Fax: 86-21-6165-2283

Yankton

1703 E. Highway 50
Yankton, SD 57078-0630 USA
Phone: 605-665-9321
Toll Free: 800-762-8800
Fax: 605-665-1709

Asia Pacific

Unit 1108, 11th Floor, APEC Plaza
48 Hoi Yuen Road
Kwun Tong, Kowloon, Hong Kong, China
Phone: 852-2866-8023
Fax: 852-2529-1822

India

Noida
SDF-D3 Zone (NSEZ) Special Economic
Noida - 201305 (U.P.)
New Delhi, India
Phone 91-120-256-2014
Fax: 91-120-256-3242

Europe

Bolwerk 26
Veldhoven – 5509 MH
Netherlands
Phone: 31-40-368-6818
Fax: 31-40-368-3501

MtronPTI may change specifications without notice to improve end application performance or product manufacturability.

No liability is assumed as a result of product use or application.

Please contact MtronPTI for latest information.

Copyright © 2014 MtronPTI