

SPECIFICATION FOR SMT LVDS OSCILLATOR MtronPTI P/N M2100S075

Electrical Specifications:

Parameter	Symbol	Min.	Тур.	Max.	Units	Conditions
Frequency of Operation	Fo		100.000000		MHz	
Frequency Tolerance		-10		+10	ppm	@ +25°C
Frequency Stability						
vs. Temperature	Δ F/F	-20		+20	ppm	
vs. Load	F∟	-1		+1	ppm	
vs. Supply Voltage	Fvs	-2		+2	ppm	
vs. Aging		-3		+3	ppm	1 st year @ +50°C
Overall Stability		-50		+50	ppm	Inclusive of initial tolerance, deviation over temperature, voltage & load variations, and 1 st year aging.
RF Output						
Output Type		Differe	ential LVDS Com	oatible		
Output Load			100 Ω Differentia		V	
Common Mode Output Voltage			1.2		V	
Differential Output Voltage		350		500	mV	LVDS Load
Symmetry (duty cycle)	T _{DC}	45		55	%	@ 50% of waveform
Rise/Fall Time	T _R /T _F			0.5	nS	From 20% to 80% Vcc
Tristate Enable Logic		80% V _{DD} or N/C			V	Pad 1: Output Enabled
Tristate Disable Logic				0.5	V	Pad 1: Output to high-Z
Start-up Time	Ts∪			10	mS	
Other Parameters						
Random Jitter	RJ			15	pS RMS	1-Sigma
Supply Voltage & Power Consumption						
Operating Voltage	Vcc	3.135	3.3	3.465	V	
Operating Current	Icc			125	mA	

Environmental Conditions:

Operating Temperature	TA	-55		+85	°C	
Storage Temperature	Ts	-55		+125	°C	
Shock	Per MIL-STD-202, Method 213, Condition C (100 g's, 6 ms duration, ½ sinewave)					
Vibration	Per MIL-STD-202, Method 201 & 204 (10 g's from 10-2000 Hz)					
Hermeticity	Per MIL-STD-202, Method 112 (1 x 10 ⁻⁸ atm cc/s of helium)					
Solderability	Per EIAJ-STD-002					
Max. Soldering Conditions	See Figure	e 1.				
Package Type	6-pad 5.0	X 7.0 X 1.9	mm leadless cera	mic. Solder ti	nned pads	(SnPb)



1703 E. Highway 50 Yankton, SD 57078 USA Phone: 800-762-8800 or 605-665-9321 Fax: 605-665-1709 Website: www.mtronpti.com

SPECIFICATION FOR SMT LVDS OSCILLATOR MtronPTI P/N M2100S075

Mechanical, Marking, and Pin Out Information:

Part Marking		
M2100S075		
1000M000		
MPTI yyww		

Legend		
уу	Year	
ww	Work week	

Solder tinned pads (SnPb)

Pin	Function
1	Enable/Disable
2	N/C
3	Ground
4	Output
5	Complementary Output
6	+V _{cc}





All dimensions

in inches [mm].

SUGGESTED SOLDER PAD LAYOUT





Figure 1

2 of 2